

**CEA-2006-A SPECIFICATIONS**

**POWER RATING: 120 Watts per channel @ 4 Ohms < 1% THD+N**  
**SN RATIO: >91 dBA (reference: 1 Watt into 4 Ohms)**

**GT Trading SPECIFICATIONS** (*Tcase = 25 °C / 4 Ohms stereo / 0.2V input level if no otherwise specified / All channels operative*)**POWER RATINGS:**

**120 Watts per channel @ 4 Ohms < 0.3% THD+N**  
**190 Watts per channel @ 2 Ohms < 0.3% THD+N**  
**380 Watts BTL mode @ 4 Ohms < 0.3% THD+N**

*Power output @ 4 Ohm / 14V4 / 1KHz / STEREO / 0.3% THD:*

**120 W x 4 – 31 A – 72 % efficiency**

*Power output @ 2 Ohm / 14V4 / 1KHz / STEREO / 0.3% THD:*

**190 W x 4 – 75 A – 69 % efficiency**

*Power output @ 4 Ohm / 14V4 / 1KHz / BRIDGE / 0.3% THD:*

**380 W x 2 – 75 A – 69% efficiency**

*THD @ 4 Ohm / 14V4 / STEREO:*

**< 0.04 % (1KHz / Power rating ref)**

*THD @ 2 Ohm / 14V4 / STEREO:*

**< 0.04 % (1KHz / Power rating ref)**

*THD @ 4 Ohm / 14V4 / BRIDGE:*

**< 0.04 % (1KHz / Power rating ref)**

*DIM @ 4 Ohm / 14V4 / STEREO:*

**< 0.003 % (Power rating ref)**

*DIM @ 2 Ohm / 14V4 / STEREO:*

**< 0.004 % (Power rating ref)**

*DIM @ 4 Ohm / 14V4 / BRIDGE:*

**< 0.004 % (Power rating ref)**

**DC-DC converter typology:**

**Regulated, PWM**

**Conversion frequency:**

**52 KHz (± 6 %)**

**Absolute maximum operation supply voltage range:**

**10 V ÷ 16 V**

**Recommended operation supply voltage range:**

**11 V ÷ 14.4 V**

**Undervoltage cutoff Threshold / delay time:**

**10 V / 60 secs.**

**Overvoltage cutoff Threshold / delay time:**

**16 V / 10 secs.**

**Mute delay time:**

**3 secs.**

**±Vcc span regulation @ 14.4 Volt:**

**54 V**

**Secondary voltages (Amp. / Bias / Pre.) @ 14.4 Volt:**

**±27 V / ±4.4 V / ±14.7 V**

**Max output offset voltage (each channel):**

**±20 mV**

**Standby current @ 14.4 Volt:**

**< 1 mA (0.7 mA typ.)**

**Quiescent consumption @ 12.6 Volt / 14.4 Volt:**

**0.9 A / 0.82 A (no idle current regulation)**

**Idle current regulation @ 14.4 Volt (4 Ohm STEREO - no signal):**

**0.1 A per channel**

**Quiescent consumption @ 12.6 Volt / 14.4 Volt:**

**1.34 A / 1.22 A (with 0.4 A total idle current regulation)**

**Thermal protection consumption @ 14.4 Volt:**

**0.9 A**

**Battery ground vs secondary ground decoupling:**

**R.C. network (22R \* 100n)**

**Body ground vs battery ground decoupling:**

**R.C. network (15R // 100n)**

**Bandwidth (-3dB ÷ 1 Watt) @ 14.4 Volt (4 Ohm STEREO):**

**5 Hz ÷ 150 KHz**

**Input sensitivity @ 14.4 Volt (4 Ohm STEREO) – Power rating ref:**

**0.2 V ÷ 5.3 V (0.2 V ÷ 5 V declared)**

**Input impedance @ 1 KHz (STEREO input):**

**10 KOhm**

**Input capacitance @ 1 KHz (STEREO input):**

**220 pF**

**Input ground decoupling:**

**R.C. network (15R // 100n)**

**S/N ratio (AP filter 10 Hz - 500 KHz) – Power rating ref:**

**91 dB**

**S/N ratio (AP filter 10 Hz - 22 KHz) – Power rating ref:**

**107 dB (“A” weighted)**

**Eq. Input noise (AP filter 10 Hz - 500 KHz):**

**5.6 uV**

**Eq. Input noise (AP filter 10 Hz - 22 KHz):**

**0.9 uV (“A” weighted)**

**Channel separation @ 100Hz / 1KHz / 10KHz – Power rating ref:**

**83 dB / 79 dB / 65 dB**

**Xover functions:**

Same features for Section A & Section B;

**HIGH Pass (15Hz – 500Hz) or LOW Pass (50Hz – 4000Hz) or BAND Pass (15Hz – 4000 Hz)**

**12 dB/oct - 0.7**

**Filter slope - Filter "Q":**

**90 / 70 °C**

**Thermal cutoff / recovery Threshold:**

**525 / 1585 (R/L section A) ÷ 488 / 1604 (R/L section B)**

**527 / 1272 (R/L section A) ÷ 530 / 1608 (R/L section B)**

**331 / 488 (R/L section A) ÷ 334 / 642 (R/L section B)**

**7.6 mOhm / 3.1 mOhm & 7.5 mOhm / 2.5 mOhm**

**Overload cutoff @ 14.4 Volt:**

**2 Ohm / 4 Ohm (Stereo / Bridged)**

**Current consumption @ 2 Ohms / 12.6 Volt / STEREO:**

**75A (Power rating ref)**

**Suggested fuse:**

**80 A**

(\*) Input signal: 1KHz, Burst 40 cycles, Interval 120 cycles, 0% Low level. Power measured after 10 cycles.